

Type 111.25CT

WIKA type 111.25CT 4½" gauges are specifically designed for the HVAC market as a contractor's gauge. This gauge features a stainless steel case, brass wetted parts, and an adjustable pointer. Contractor's gauges are designed for static applications and may not be well-suited to high vibration and pulsation applications.



MECHANICAL PRESSURE

Standard Features

- | | | | |
|----------------------|-------------------------------|--------------------|----------------------------|
| Size: | 4½" | Pointer: | Black aluminum, adjustable |
| Case: | Stainless steel, matte-finish | Accuracy: | ± 1% of span |
| Wetted Parts: | Copper alloy | | ASME B40.100 Grade 1A |
| Window: | Snap-in polycarbonate | Connection: | Lower mount |
| Dial: | White aluminum | | |

Type	111.25CT	
Size	4½"	
Connection	LM	
Conn. Size	1/4" NPT	
Press. Scale	PSI	PSI/KPA
30" Hg		
30"-0-15 psi	4277687	4277849
30"-0-30 psi	4277695	4277857
30"-0-60 psi	4277709	4277865
30"-0-100 psi	4277717	4277873
30"-0-160 psi	4277725	4277881
30"-0-200 psi	4277733	4277890
30"-0-300 psi	4277741	4277903
30"-0-400 psi		
15 psi	4277750	4277911
30 psi	4277768	4277920
60 psi	4277776	4277938
100 psi	4277784	4277946
160 psi	4277792	4277954
200 psi	4277806	4277962
300 psi	4277814	4277971
400 psi	4277822	4277989
600 psi	4277831	4277997
Accessory order codes (installed at factory)		
Rear flange, SS	+ RF	
Restrictor	+ R	

Available Options

- Cleaned for oxygen service
- Special connections
- Restrictor
- Stainless steel case with rear flange
- Black steel case

Abbreviations

LM - Lower mount
 SS - Stainless steel

Stock items shown in blue print.